



Retrofit of SPC-1 Hospital Buildings to SPC-2


Roy Lobo, Principal Structural Engineer
OSHPD

January 16-17, 2014 - University of California, Los Angeles

Earthquake Damage to Concrete Hospital Buildings (1971 Sylmar)



Most of California's hospital buildings were constructed prior to the 1973 Hospital Seismic Safety Act (HSSA).



HSSA 1983

“129675. This chapter shall be known and may be cited as the Alfred E. Alquist Hospital Facilities Seismic Safety Act of 1983. 129680.

(a) It is the intent of the Legislature that hospital buildings that house patients who have less than the capacity of normally healthy persons to protect themselves, and that must be reasonably capable of providing services to the public after a disaster, shall be designed and constructed to resist, insofar as practical, the forces generated by earthquakes, gravity, and winds. In order to accomplish this purpose, the office shall propose proper building standards for earthquake resistance based upon current knowledge, and provide an independent review of the design and construction of hospital buildings. “

Common Deficiencies in Non-Ductile Concrete Buildings

Soft story

Weak Story

Vertical Discontinuities

Torsion

Redundancy

Defection Incompatibility

Shear failure

Strong Column/Weak Beam

Coupling Beams

Overturning

Case Study: SPC-1 Hospital Building




Building Description

- Constructed in 1960's
- Five stories plus basement
- Gravity System
 - Reinforced concrete pan joist system
 - Interior reinforced concrete columns
 - Perimeter reinforced concrete bearing/shear walls
 - Isolated and continuous spread reinforced concrete foundations
- Lateral System
 - 8" thick perforated reinforced concrete bearing/shear walls
 - Continuous spread reinforced concrete foundations
- Unique Issues
 - "Weakened plane joints" = 1.75" reveals with $\frac{2}{3}$ of horizontal rebar cut
 - Wall piers do not have hooks on horizontal bars

Non-conforming SPC-1

Conventional Retrofit Design



Conventional Retrofit Design



Wall Elevation




Wall Elevation



Indicates 24" of reinforced concrete wall thickening


Conventional Retrofit Design




Foundation Plan

Indicates new 14 ft wide by 6 ft deep reinforced concrete foundations

Studying Potential Mechanisms




Soft Story Mechanism







Rocking Mechanism

Perform Model




Non-linear Pushover Analysis

PUSH



Component Testing Program

- Consists of representative shear wall spandrels and piers
- Purpose is to provide more representative backbone curves than provided by FEMA-356
- Involve OSHPD in testing through approved testing criteria and observation of tests






UCLA Lab Testing Setup




Spandrel Test Results




Tested vs. Assumed Backbone Curves (Spandrels)



Retrofit using non-linear analysis



Retrofit using Nonlinear Analysis




Wall Elevation

Wall Elevation



Indicates 8" of concrete thickening or concrete "catch" mechanisms above building exits

Retrofit using Nonlinear Analysis







Foundation Plan



Indicates approximately 18" of concrete footing thickening

Non-linear Pushover Analysis

PUSH



Risk Targeted Retrofit to SPC-2

- Where the Office has performed a collapse probability assessment, and the Probability of Collapse is less than or equal to 1.20% (HAZUS)
- Could required mitigation of some significant structural deficiencies.

Significant Structural Deficiencies pertinent to Concrete Buildings

- Short Captive Column
- Weak Story
- Soft Story
- Torsion
- Deflection Incompatibility
- Vertical Discontinuity
- Weak Columns
- Load Path

Case Study – Collapse Probability

Building Height = 65'-8"

Building Type = C1M,
Concrete Moment Frame

Code Year = 1964

Deficiencies = Weak Column Concrete,
Deflection Incompatibility

Fault Distance = 10.7 km

Fault Magnitude = 7.0

Zone = 4

Sa03 = 1.498 g

Sa10 = 0.533 g





Building Input Parameters

Response Parameter	Case a (No Deficiencies)	Case b (With Deficiencies)
Building Capacity		
$A_y =$	0.09	0.09
$D_y =$	0.96	0.96
$A_u =$	0.19	0.16
$D_u =$	6.95	6.08
Building Response		
$\kappa =$	0.6	0.4
Building Fragility		
$S_{DC} =$	19.29	16.08
$\beta =$	0.81	0.91
Collapse Rate Factor		
$P[\text{COL} \text{STR}_5] =$	0.13	0.25


Collapse Probability, with Deficiencies

$S_d = 6.18$ inches, $P|Col = 3.67\%$



Collapse Probability, No Deficiencies

$S_d = 4.89$ inches, $P|Col = 0.59\%$



Common Retrofit Techniques

- FRP
- New Shear Walls
- Concrete jacketing
- Dampers
- Alternate methods for shear enhancement

Questions ?

